

| FMD Prover Flow Rates and Displaced Volume | | | | | | | | | | | | | | |
|---|----------|-----------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|-----|
| FMD Model Number | | FMD-001 | FMD-003 | FMD-007 | FMD-015 | FMD-025 | FMD-035 | FMD-045 | FMD-060 | FMD-090 | FMD-130 | FMD-200 | FMD-245 | |
| Max Flow Rate | GPM | 100 | 300 | 700 | 1,500 | 2,500 | 3,500 | 4,500 | 6,000 | 9,000 | 13,000 | 20,000 | 24,500 | |
| | BPH | 142 | 428 | 1,000 | 2,100 | 3,570 | 5,000 | 6,400 | 8,500 | 12,850 | 18,500 | 28,500 | 35,000 | |
| | M3/HR | 23 | 68 | 150 | 330 | 560 | 790 | 1,022 | 1,350 | 2,000 | 2,900 | 4,500 | 5,565 | |
| *Displaced Volume | Gallons | Primary | 0.75 | 2 | 5 | 10 | 20 | 25 | 35 | 50 | 80 | 90 | 130 | 168 |
| | | Secondary | 0.35 | 1 | 4 | 8 | 15 | 20 | 25 | 40 | 60 | 60 | 100 | 126 |
| | **Litres | Primary | 2.9 | 7.5 | 19 | 38 | 76 | 95 | 132 | 190 | 303 | 341 | 492 | 636 |
| | | Secondary | 1.3 | 3.8 | 15 | 30 | 57 | 76 | 95 | 151 | 227 | 227 | 379 | 477 |
| <p>*Please note: Standard prover volume is in gallons, litres are optional</p> <p>**Litres are a direct conversion and not indicative of volumetric calibration can sizes</p> | | | | | | | | | | | | | | |
| Inlet / Outlet Flange Size (ANSI B 16.5) | | 1" | 2" | 3" | 4" | 6" | 6" | 8" | 10" | 12" | 16" | 20" | 24" | |