

Dimensions - Hex Head Bolts

	D	L	H	W
BT05	0.5 mm	3.0 mm	0.4 mm	0.8 mm
BT05s	0.5 mm	3.0 mm	0.4 mm	0.8 mm
BT06	0.6 mm	4.0 mm	0.6 mm	1.0 mm
BT06n	0.6 mm	4.0 mm	0.6 mm	1.0 mm
BT065	0.6 mm	5.0 mm	0.6 mm	1.0 mm
BT066	0.6 mm	6.0 mm	0.6 mm	1.0 mm
BT08	0.8 mm	2.0 mm	0.5 mm	1.0 mm
BT08s	0.8 mm	2.0 mm	0.5 mm	1.0 mm
BT086	0.8 mm	6.0 mm	0.8 mm	1.3 mm
BT086s	0.8 mm	6.0 mm	0.8 mm	1.3 mm
BT103	1.0 mm	3.0 mm	0.8 mm	1.4 mm
BT103s	1.0 mm	3.0 mm	0.8 mm	1.4 mm
BT108	1.0 mm	8.0 mm	1.0 mm	1.5 mm
BT108n	1.0 mm	8.0 mm	1.0 mm	1.5 mm
BT12	1.2 mm	8.0 mm	1.0 mm	2.0 mm
BT12n	1.2 mm	8.0 mm	1.0 mm	2.0 mm
BT14	1.4 mm	8.0 mm	1.0 mm	2.0 mm
BT14n	1.4 mm	8.0 mm	1.0 mm	2.0 mm
BT1412	1.4 mm	12.0 mm	1.4 mm	2.0 mm
BT1412n	1.4 mm	12.0 mm	1.4 mm	2.0 mm
BT16	1.6 mm	12.0 mm	1.1 mm	2.5 mm
BT16n	1.6 mm	12.0 mm	1.1 mm	2.5 mm
BT164	1.6 mm	4.0 mm	1.1 mm	2.5 mm
BT166	1.6 mm	6.0 mm	1.1 mm	2.5 mm
BT166n	1.6 mm	6.0 mm	1.1 mm	2.5 mm
BT210	2.0 mm	10.0 mm	1.3 mm	3.0 mm
BT210n	2.0 mm	10.0 mm	1.3 mm	3.0 mm
BT212	2.0 mm	12.0 mm	1.3 mm	3.0 mm
BT212n	2.0 mm	12.0 mm	1.3 mm	3.0 mm
BT215s	2.0 mm	15.0 mm	1.3 mm	3.0 mm
BT25	2.5 mm	8.0 mm	1.5 mm	3.5 mm
BT25n	2.5 mm	8.0 mm	1.5 mm	3.5 mm
BT80	#0-80	0.500"	.042"	.0937"
BT80n	#0-80	0.500"	.042"	.0937"
BT802.5	#0-80	0.250"	.042"	.0937"
BT90	#00-90	0.500"	.042"	.0781"
BT90n	#00-90	0.500"	.042"	.0781"

