



## ASSEMBLY LIST

- ① 8"Ø INLET, FLANGED
- ② 8"Ø OUTLET, FLANGED
- ③ 4"Ø FPT DUPLEX SERVICE FITTING
- ④ 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- ⑤ COALESCING MEDIA
- ⑥ SLUDGE BAFFLE
- ⑦ 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- ⑧ LIFTING LUGS
- ⑨ OPTIONAL PREFABRICATED DEADMAN

### WEIGHTS & CAPACITIES

10'Ø - 12,000 GAL. TANK SW OR DW  
 NOMINAL WGT. SW 6,000#  
 NOMINAL WGT. DW 7,600#  
 MAX. SPILL CAPACITY 7,200 GAL.

MODEL: HB-F-10-12K-2 228 G.P.M.	OWS JOB No. -		<b>OIL WATER SEPARATOR          TECHNOLOGIES, LLC</b> 1109 25TH STREET W.P.B., FL. 33407
	JOB: OWS TECHNOLOGIES	DRAWING No. 4S5100 FILE: 10-12K-228-SWDW 12/22/14	SCALE: N.T.S. DATE: 12/22/14

THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES, 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.