



ASSEMBLY LIST

- ① 10"Ø INLET, FLANGED
- ② 10"Ø OUTLET, FLANGED
- ③ 4"Ø FPT DUPLEX SERVICE FITTING
- ④ 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- ⑤ COALESCING MEDIA
- ⑥ SLUDGE BAFFLE
- ⑦ 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- ⑧ LIFTING LUGS
- ⑨ OPTIONAL PREFABRICATED DEADMAN

WEIGHTS & CAPACITIES

10'Ø - 12,000 GAL. TANK SW OR DW
 NOMINAL WGT. SW 6,000#
 NOMINAL WGT. DW 7,600#
 MAX. SPILL CAPACITY 7,200 GAL.

OIL WATER SEPARATOR TECHNOLOGIES, LLC 1109 25TH STREET W.P.B., FL. 33407	SCALE: N.T.S.	DRAWN BY: TMB
	DATE: 12/22/14	CHECKED BY:
MODEL: HB-F-10-12K-5 570 G.P.M.	OWS JOB No. -	DRAWING No. 4S5097
JOB: OWS TECHNOLOGIES	FILE: 10-12K-570-SWDW 12/22/14	

