



ASSEMBLY LIST

- 1 14"Ø INLET, FLANGED
- 2 14"Ø OUTLET, FLANGED
- 3 4"Ø FPT DUPLEX SERVICE FITTING
- 4 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- 5 COALESCING MEDIA
- 6 SLUDGE BAFFLE
- 7 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- 8 LIFTING LUGS
- 9 OPTIONAL PREFABRICATED DEADMAN

SCALE: N.T.S. DATE: 12/23/14
THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES 1109 25TH STREET WEST PALM BEACH, FL 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.

OIL WATER SEPARATOR
TECHNOLOGIES LLC
 1109 25TH STREET W.P.B., FL. 33407

MODEL: HB-F-10-20K-10 1,140 G.P.M.
 JOB: OWS TECHNOLOGIES
 OWS JOB No. -
 DRAWING No. 4S5119
 FILE: 10-20K-1140-SWDW 12/23/14

WEIGHTS & CAPACITIES

10'Ø - 20,000 GAL. TANK SW OR DW
 NOMINAL WGT. SW 10,900#
 NOMINAL WGT. DW 13,400#
 MAX. SPILL CAPACITY 12,000 GAL.