



## ASSEMBLY LIST

- 1 14"Ø INLET, FLANGED
- 2 14"Ø OUTLET, FLANGED
- 3 4"Ø FPT DUPLEX SERVICE FITTING
- 4 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- 5 COALESCING MEDIA
- 6 SLUDGE BAFFLE
- 7 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- 8 LIFTING LUGS
- 9 OPTIONAL PREFABRICATED DEADMAN

<b>OIL WATER SEPARATOR</b> <b>TECHNOLOGIES LLC</b> 1109 25TH STREET W.P.B., FL. 33407	SCALE: N.T.S.	DRAWN BY: TMB
	DATE: 12/23/14	CHECKED BY:
MODEL: HB-F-10-20K-12 1,368 G.P.M.	OWS JOB No. -	DRAWING No. 4S5117
JOB: OWS TECHNOLOGIES	FILE: 10-20K-1368-SWOW 12/23/14	OWS TECHNOLOGIES

## WEIGHTS & CAPACITIES

10'Ø - 20,000 GAL. TANK SW OR DW  
 NOMINAL WGT. SW 10,900#  
 NOMINAL WGT. DW 13,400#  
 MAX. SPILL CAPACITY 12,000 GAL.