



ASSEMBLY LIST

- 1 18"Ø INLET, FLANGED
- 2 18"Ø OUTLET, FLANGED
- 3 4"Ø FPT DUPLEX SERVICE FITTING
- 4 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- 5 COALESCING MEDIA
- 6 SLUDGE BAFFLE
- 7 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- 8 LIFTING LUGS
- 9 OPTIONAL PREFABRICATED DEADMAN

**OIL WATER SEPARATOR
TECHNOLOGIES LLC**
1109 25TH STREET W.P.B., FL. 33407

OWS JOB No. -
DRAWING No. 4S5024
FILE: 10-20K-2166-SWDW 1/31/14

MODEL: HB-F-10-20K-19 2,166 G.P.M.
JOB: OWS TECHNOLOGIES

SCALE: N.T.S.
DATE: 1/31/14
DRAWN BY: TMB
CHECKED BY:

THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.

WEIGHTS & CAPACITIES

10'Ø - 20,000 GAL. TANK SW OR DW
NOMINAL WGT. SW 10,900#
NOMINAL WGT. DW 13,400#
MAX. SPILL CAPACITY 12,000 GAL.