


ASSEMBLY LIST

- 1 16"Ø INLET, FLANGED
- 2 16"Ø OUTLET, FLANGED
- 3 4"Ø FPT DUPLEX SERVICE FITTING
- 4 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- 5 COALESCING MEDIA
- 6 SLUDGE BAFFLE
- 7 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- 8 LIFTING LUGS
- 9 OPTIONAL PREFABRICATED DEADMAN

<p>MODEL: HB-F-10-25K-17 1,938 G.P.M.</p> <p>JOB: OWS TECHNOLOGIES</p>	<p>OWS JOB No. -</p> <p>DRAWING No. 4S5137</p> <p>FILE: 10-25K-1938-SWDW 12/30/14</p>
 <p>OWS TECH TECHNOLOGIES LLC 1109 25TH STREET W.P.B., FL. 33407</p>	
<p>SCALE: N.T.S.</p> <p>DATE: 12/30/14</p>	<p>THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.</p> <p>DRAWN BY: TMB</p> <p>CHECKED BY:</p>

WEIGHTS & CAPACITIES

10'Ø - 25,000 GAL. TANK SW OR DW
 NOMINAL WGT. SW 15,000#
 NOMINAL WGT. DW 17,700#
 MAX. SPILL CAPACITY 15,000 GAL.