

ASSEMBLY LIST


- 1 18"Ø INLET, FLANGED
- 2 18"Ø OUTLET, FLANGED
- 3 4"Ø FPT DUPLEX SERVICE FITTING
- 4 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- 5 COALESCING MEDIA
- 6 SLUDGE BAFFLE
- 7 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- 8 LIFTING LUGS
- 9 OPTIONAL PREFABRICATED DEADMAN

THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES, 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.

SCALE: N.T.S.
DATE: 12/30/14

DRAWN BY: TMB
CHECKED BY:

OIL WATER SEPARATOR
TECHNOLOGIES, LLC
1109 25TH STREET W.P.B., FL. 33407



OWS JOB No. -
DRAWING No. 4S5130
FILE: 10-25K-2850-SWDW 12/30/14

MODEL: HB-F-10-25K-25 2,850 G.P.M.
JOB: OWS TECHNOLOGIES

WEIGHTS & CAPACITIES

10'Ø - 25,000 GAL. TANK SW OR DW
NOMINAL WGT. SW 15,000#
NOMINAL WGT. DW 17,700#
MAX. SPILL CAPACITY 15,000 GAL.