


ASSEMBLY LIST

- 1 20"Ø INLET, FLANGED
- 2 20"Ø OUTLET, FLANGED
- 3 4"Ø FPT DUPLEX SERVICE FITTING
- 4 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- 5 COALESCING MEDIA
- 6 SLUDGE BAFFLE
- 7 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- 8 LIFTING LUGS
- 9 OPTIONAL PREFABRICATED DEADMAN

OIL WATER SEPARATOR TECHNOLOGIES LLC
 1109 25TH STREET W.P.B., FL. 33407



OWS JOB No. -

MODEL: HB-F-10-25K-27 3,078 G.P.M.

DRAWING No. 4S5129
 FILE: 10-25K-3078-SWDW 12/30/14

JOB: OWS TECHNOLOGIES

SCALE: N.T.S. DATE: 12/30/14
 THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.
 DRAWN BY: TMB
 CHECKED BY:

WEIGHTS & CAPACITIES

10'Ø - 25,000 GAL. TANK SW OR DW
 NOMINAL WGT. SW 15,000#
 NOMINAL WGT. DW 17,700#
 MAX. SPILL CAPACITY 15,000 GAL.