



ASSEMBLY LIST

- ① 20"Ø INLET, FLANGED
- ② 20"Ø OUTLET, FLANGED
- ③ 4"Ø FPT DUPLEX SERVICE FITTING
- ④ 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- ⑤ COALESCING MEDIA
- ⑥ SLUDGE BAFFLE
- ⑦ 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- ⑧ LIFTING LUGS
- ⑨ OPTIONAL PREFABRICATED DEADMAN

THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES, 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.

SCALE: N.T.S.
DATE: 1/30/14

DRAWN BY: TMB
CHECKED BY:

OIL WATER SEPARATOR TECHNOLOGIES LLC
1109 25TH STREET W.P.B., FL. 33407

OWS JOB No. -
DRAWING No. 4S5023
FILE: 10-25K-3192-SWDW 1/30/14

MODEL: HB-F-10-25K-28 3,192 G.P.M.
JOB: OWS TECHNOLOGIES

WEIGHTS & CAPACITIES

10'Ø - 25,000 GAL. TANK SW OR DW
NOMINAL WGT. SW 15,000#
NOMINAL WGT. DW 17,700#
MAX. SPILL CAPACITY 15,000 GAL.