



## ASSEMBLY LIST

- ① 12"Ø INLET, FLANGED
- ② 12"Ø OUTLET, FLANGED
- ③ 4"Ø FPT DUPLEX SERVICE FITTING
- ④ 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- ⑤ COALESCING MEDIA
- ⑥ SLUDGE BAFFLE
- ⑦ 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- ⑧ LIFTING LUGS
- ⑨ OPTIONAL PREFABRICATED DEADMAN

THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES, 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.

SCALE: N.T.S. DATE: 12/30/14

DRAWN BY: TMB  
CHECKED BY:

**OIL WATER SEPARATOR  
TECHNOLOGIES, LLC**

1109 25TH STREET W.P.B., FL. 33407



OWS JOB No. -

DRAWING No. 4S5148  
FILE: 10-25K-684-SWDW 12/30/14

MODEL: HB-F-10-25K-6 684 G.P.M.

JOB: OWS TECHNOLOGIES

## WEIGHTS & CAPACITIES

10'Ø - 25,000 GAL. TANK SW OR DW  
 NOMINAL WGT. SW 15,000#  
 NOMINAL WGT. DW 17,700#  
 MAX. SPILL CAPACITY 15,000 GAL.