



- ① 6"Ø INLET, FLANGED
- ② 6"Ø OUTLET, FLANGED
- ③ 4"Ø FPT DUPLEX SERVICE FITTING
- ④ 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- ⑤ COALESCING MEDIA
- ⑥ SLUDGE BAFFLE
- ⑦ 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR
- ⑧ LIFTING LUGS
- ⑨ OPTIONAL PREFABRICATED DEADMAN

WEIGHTS & CAPACITIES
 6'Ø - 3,000 GAL. TANK DW
 NOMINAL WGT. DW 2,700#
 MAX. SPILL CAPACITY 1,800 GAL.

MODEL: HB-F-6-3K-1 73 G.P.M. JOB: OWS TECHNOLOGIES	OWS JOB No. -	OIL WATER SEPARATOR TECHNOLOGIES LLC 1109 25TH STREET W.P.B., FL. 33407	SCALE: N.T.S.	DRAWN BY: TMB
	DRAWING No. 4S5043 FILE: 6-3K-73-DW 12/18/14		DATE: 12/18/14	CHECKED BY:

THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES, 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.