



ASSEMBLY LIST

- ① 6"Ø INLET, FLANGED
- ② 6"Ø OUTLET, FLANGED
- ③ 4"Ø FPT DUPLEX SERVICE FITTING
- ④ 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- ⑤ COALESCING MEDIA
- ⑥ SLUDGE BAFFLE
- ⑦ 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- ⑧ LIFTING LUG
- ⑨ OPTIONAL PREFABRICATED DEADMAN

SCALE: N.T.S.	DATE: 12/18/14	DRAWN BY: TMB
		CHECKED BY:

OIL WATER SEPARATOR
TECHNOLOGIES, LLC
 1109 25TH STREET W.P.B., FL. 33407

MODEL: HB-F-6-4K-2 146 G.P.M. DW	OWS JOB No. -
JOB: OWS TECHNOLOGIES	DRAWING No. 4S5047 FILE: 6-4K-146-DW 12/18/14

WEIGHTS & CAPACITIES

6'Ø - 4,000 GAL. TANK DW
 NOMINAL WGT. DW 4,900#
 MAX. SPILL CAPACITY 2,400 GAL.