



## ASSEMBLY LIST

- 1 6"Ø INLET, FLANGED
- 2 6"Ø OUTLET, FLANGED
- 3 4"Ø FPT DUPLEX SERVICE FITTING
- 4 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- 5 COALESCING MEDIA
- 6 SLUDGE BAFFLE
- 7 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- 8 LIFTING LUGS
- 9 OPTIONAL PREFABRICATED DEADMAN

SCALE: N.T.S. DATE: 12/18/14

THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES, 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.

DRAWN BY: TMB  
CHECKED BY:

**OIL WATER SEPARATOR**  
**TECHNOLOGIES, LLC**  
1109 25TH STREET W.P.B., FL. 33407

MODEL: HB-F-8-6K-2 152 G.P.M.

JOB: OWS TECHNOLOGIES

OWS JOB No. -

DRAWING No. 4S5055  
FILE: 8-6K-152-SWOW 12/18/14

## WEIGHTS & CAPACITIES

8'Ø - 6,000 GAL. TANK SW OR DW  
NOMINAL WGT. SW 4,800#  
NOMINAL WGT. DW 5,700#  
MAX. SPILL CAPACITY 3,600 GAL.