



ASSEMBLY LIST

- 1 6"Ø INLET, FLANGED
- 2 6"Ø OUTLET, FLANGED
- 3 4"Ø FPT DUPLEX SERVICE FITTING
- 4 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- 5 COALESCING MEDIA
- 6 SLUDGE BAFFLE
- 7 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- 8 LIFTING LUGS
- 9 OPTIONAL PREFABRICATED DEADMAN



**OIL WATER SEPARATOR
TECHNOLOGIES LLC**
1109 25TH STREET W.P.B., FL. 33407

SCALE: N.T.S.
DATE: 12/18/14

THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES, 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.

DRAWN BY: TMB
CHECKED BY:

OWS JOB No. -

MODEL: HB-F-8-6K-1 76 G.P.M.

DRAWING No. 4S5056
FILE: 8-6K-76-SWDW 12/18/14

JOB: OWS TECHNOLOGIES

WEIGHTS & CAPACITIES

8'Ø - 6,000 GAL. TANK SW OR DW
NOMINAL WGT. SW 4,800#
NOMINAL WGT. DW 5,700#
MAX. SPILL CAPACITY 3,600 GAL.