



### ASSEMBLY LIST

- ① 10"Ø INLET, FLANGED
- ② 10"Ø OUTLET, FLANGED
- ③ 4"Ø FPT DUPLEX SERVICE FITTING
- ④ 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- ⑤ COALESCING MEDIA
- ⑥ SLUDGE BAFFLE
- ⑦ 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- ⑧ LIFTING LUGS
- ⑨ OPTIONAL PREFABRICATED DEADMAN

### WEIGHTS & CAPACITIES

8'Ø - 6,000 GAL. TANK SW OR DW  
 NOMINAL WGT. SW 4,800#  
 NOMINAL WGT. DW 5,700#  
 MAX. SPILL CAPACITY 3,600 GAL.

MODEL: HB-F-8-6K-5 380 G.P.M.	OWS JOB No. -		<b>OIL WATER SEPARATOR          TECHNOLOGIES, LLC</b> 1109 25TH STREET W.P.B., FL. 33407	DRAWN BY: TMB	THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES, 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.
	JOB: OWS TECHNOLOGIES			DRAWING No. 3S5039 FILE: 8-6K-380-SWOW 7/10/13	