



ASSEMBLY LIST

- ① 6"Ø INLET, FLANGED
- ② 6"Ø OUTLET, FLANGED
- ③ 4"Ø FPT DUPLEX SERVICE FITTING
- ④ 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- ⑤ COALESCING MEDIA
- ⑥ SLUDGE BAFFLE
- ⑦ 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- ⑧ LIFTING LUGS
- ⑨ OPTIONAL PREFABRICATED DEADMAN

WEIGHTS & CAPACITIES

8'Ø - 8,000 GAL. TANK SW OR DW
 NOMINAL WGT. SW 5,300#
 NOMINAL WGT. DW 6,400#
 MAX. SPILL CAPACITY 4,800 GAL.

MODEL: HB-F-8-8K-2 152 G.P.M. JOB: OWS TECHNOLOGIES	OWS JOB No. —	DRAWING No. 4S5062 FILE: 8-8K-152-SWOW 12/18/14		OIL WATER SEPARATOR TECHNOLOGIES, LLC 1109 25TH STREET W.P.B., FL. 33407	SCALE: N.T.S. DATE: 12/18/14	THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.	DRAWN BY: TMB CHECKED BY:
	OWS TECHNOLOGIES						