



### ASSEMBLY LIST

- ① 12"Ø INLET, FLANGED
- ② 12"Ø OUTLET, FLANGED
- ③ 4"Ø FPT DUPLEX SERVICE FITTING
- ④ 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- ⑤ COALESCING MEDIA
- ⑥ SLUDGE BAFFLE
- ⑦ 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- ⑧ LIFTING LUGS
- ⑨ OPTIONAL PREFABRICATED DEADMAN

SCALE: N.T.S.  
DATE: 12/18/14

THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES, 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.

DRAWN BY: TMB  
CHECKED BY:

**OIL WATER SEPARATOR**  
**TECHNOLOGIES, LLC**  
1109 25TH STREET W.P.B., FL. 33407

MODEL: HB-F-8-8K-8 608 G.P.M.

JOB: OWS TECHNOLOGIES

OWS JOB No. -  
DRAWING No. 4S5058  
FILE: 8-8K-608-SWOW 12/18/14

### WEIGHTS & CAPACITIES

8'Ø - 8,000 GAL. TANK SW OR DW  
NOMINAL WGT. SW 5,300#  
NOMINAL WGT. DW 6,400#  
MAX. SPILL CAPACITY 4,800 GAL.