



ASSEMBLY LIST

- ① 12"Ø INLET, FLANGED
- ② 12"Ø OUTLET, FLANGED
- ③ 4"Ø FPT DUPLEX SERVICE FITTING
- ④ 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- ⑤ COALESCING MEDIA
- ⑥ SLUDGE BAFFLE
- ⑦ 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- ⑧ LIFTING LUGS
- ⑨ OPTIONAL PREFABRICATED DEADMAN

MODEL: HB-F-8-8K-9 684 G.P.M.
 JOB: OWS TECHNOLOGIES
 OWS JOB No. —
 DRAWING No. 4S5021
 FILE: 8-8K-684-SWOW 1/30/14

OIL WATER SEPARATOR
TECHNOLOGIES, LLC
 1109 25TH STREET W.P.B., FL. 33407

SCALE: N.T.S.
 DATE: 1/30/14

DRAWN BY: TMB
 CHECKED BY:

THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.

WEIGHTS & CAPACITIES

8'Ø - 8,000 GAL. TANK SW OR DW
 NOMINAL WGT. SW 5,300#
 NOMINAL WGT. DW 6,400#
 MAX. SPILL CAPACITY 4,800 GAL.