



### ASSEMBLY LIST

- ① 12"Ø INLET, FLANGED
- ② 12"Ø OUTLET, FLANGED
- ③ 4"Ø FPT DUPLEX SERVICE FITTING
- ④ 2'-6"Ø MANWAY W/ (2) FPT FITTINGS
- ⑤ COALESCING MEDIA
- ⑥ SLUDGE BAFFLE
- ⑦ 4"Ø FPT MONITOR FITTING OR OPTIONAL HYDROSTATIC RESERVOIR (DW ONLY)
- ⑧ LIFTING LUGS
- ⑨ OPTIONAL PREFABRICATED DEADMAN

### WEIGHTS & CAPACITIES

8'Ø - 8,000 GAL. TANK SW OR DW  
 NOMINAL WGT. SW 5,300#  
 NOMINAL WGT. DW 6,400#  
 MAX. SPILL CAPACITY 4,800 GAL.

<b>OIL WATER SEPARATOR</b> <b>TECHNOLOGIES, LLC</b> 1109 25TH STREET W.P.B., FL. 33407	OWS JOB No. —	MODEL: HB-F-8-8K-11 836 G.P.M.	DRAWN BY: TMB
	DRAWING No. 355040 FILE: 8-8K-836-SWOW 7/10/13	JOB: OWS TECHNOLOGIES	SCALE: N.T.S. DATE: 7/10/13

THIS DRAWING AND SPECIFICATION IS THE PROPERTY OF OWS TECHNOLOGIES, 1109 25TH STREET WEST PALM BEACH, FL. 33407 AND SHALL NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION.