



WIRELESS DECT™ IP PHONE SOLUTION

BENEFITS

- Rest assured that your devices stay cleaner for longer with integrated Microban® antimicrobial product protection
- Maintain confidence that your devices will last and that your investment is protected: The ruggedized handsets are drop proof (up to 6.6 ft/2 m) and IP65 dust-tight and water resistant
- Conversations are safe and secure with DECT™ wireless security that maintains DECT™ encryption even in repeater mode
- Scale as you grow: Choose from various quantities of handsets to meet your organization's needs and shift sizes
- Communicate hands-free with a Poly headset using the built-in Bluetooth® on Poly Rove 40 or the 3.5 mm connection on Poly Rove 30 and Poly Rove 40

POLY ROVE FAMILY

Keep the conversation going whenever, wherever—at work. Built for on-site employees the Poly Rove wireless IP phone solution delivers the sweet freedom to move and the flexibility to scale as you grow. Dropped phone? No problem. You're covered with ruggedized IP65, dust-tight, and water-resistant technology. Protection doesn't stop there. Built to stay cleaner for longer with Microban® antimicrobial product protection. And guard your most critical conversations with DECT™ technology. We've got you covered. Built to last. Built to scale. Never miss a call.

- Integrated Microban® antimicrobial product protection
- Ruggedized IP65-rated handsets
- Secure DECT™ encryption, even in repeater mode
- Highly scalable system
- Operable with Poly hands-free headsets
- Cloud device management software (available through service providers, some services sold separately)

POLY ROVE R8 DECT™ REPEATER



SPECIFICATIONS

DECT™ FREQUENCY

- 1920-1930 MHz (North America SKU)
- 1880-1900 MHz (EU/ANZ/UK SKU)

RANGE

- Indoor: up to 165 ft (50 m)
- Outdoor: up to 980 ft (300 m)
- Range increases by up to 50 m or up to 300 m depending on environment as a base station or repeater is added

GENERAL FEATURES

- Extends DECT™ coverage
- Supports automatic handover of calls
- Up to 2 simultaneous calls per repeater
- Up to 6 repeaters per base station
- Up to 3 repeaters in cascade mode
- Automatic Handover of Calls between Cells
- Air synchronization
- Encrypted Daisy Chained
- Auto Configuration on Single and Dual Cell
- Zero Touch Installation
- 12 Slot Support
- DECT™ Security Step B
- LED Indicator

PHYSICAL FEATURES

- External Universal AC adapter (5V 2A DC)
- Wall Mountable

POLY ROVE R8 DECT™ REPEATER COMES WITH:

- Repeater
- Stand
- Power Adapter
- Wall Mounting Kit
- Quick Start Card
- Safety Sheet²

COMPLIANCE

- USA FCC
- Canada IC RSS
- EEA CE
- AU/NZ RCM
- NZ Telepermit
- Hong Kong HKCA
- Singapore IMDA TS CT-CTS
- ROHS compliant
- ENERGY STAR

SAFETY

- UL 62368-1
- CE Mark
- CAN/CSA C22.2 No 62368-1
- EN 60950-1 and 62368-1
- IEC 60950-1 and 62368-1
- AS/NZS 60950.1 and 62368.1

OPERATING CONDITIONS

- Temperature: -10 to +55°C (+14 to +131°F)
- Relative humidity: 5% to 95%, non-condensing
- Storage Temperature: -40 to +70°C (-40 to +158° F)

WEIGHT

- Repeater weight: 0.166 kg

UNIT BOX DIMENSIONS (W X H X D)/WEIGHT

- Repeater box dimensions: 239 x 141 x 44 (mm)
- Repeater box weight: 0.354 kg (with product, accessory, and documents)

MASTER CARTON QUANTITY

- 10

COUNTRY OF ORIGIN

- China

WARRANTY

- 1-year limited warranty

¹Most software-enabled features and capabilities must be supported by the server. Please contact your IP PBX/softswitch vendor or service provider for a list of supported features.

²Safety sheets are only included in EU units.

LEARN MORE

For more information on Poly Rove Family, visit poly.com/rove