

Maintenance and Operation Manual for Aviation Platform Stand

DF071556-03(XP)

Liftsafe Fall Protection Inc.

Aviation Platform Stand Manual

Table of Contents

Sect	ion	Page Number
1.0	Standards	3
2.0	Electrical Hazard	4
3.0	Safety Precautions	5
4.0	Inspections	7
5.0	First Use Instructions	8
6.0	Maintenance, Inspection and Service	8
7.0	Replacement Parts List	12
8.0	Regular Operation Procedure	14
9.0	Notes	17



1.0 Standards

Tested in general accordance with the applicable requirements of

• DIN EN 131 — 2:2012

• BS EN 131 - 7:2013

• ANSI – ASC A14.7 – 20 – 2011

The best insurance against an accident is a careful, qualified operator. Most accidents are caused by the failure of individuals to follow simple and fundamental safety rules and precautions. Use common sense when operating a mobile ladder stand.

You, as a careful operator, are the best insurance against an accident. Therefore, proper usage of this Aviation Platform Stand is mandatory. The following pages of this manual should be read and understood completely before operating the Aviation Platform Stand.

Common sense dictates the use of protective clothing when working on or near machinery. Use appropriate safety devices to protect your eyes, ears, hands, feet and body.

Any modifications from the original design are strictly forbidden without written permission from Liftsafe Engineering and Service Group Inc.





2.0 Electrocution Hazard

This Aviation Platform Stand is not electrically insulated. Maintain a Minimum Safe Approach Distance (MSAD) from energized power lines and parts as listed below. The operator must allow for the ladder to sway, rock or sag. This mobile ladder stand does not provide protection from contact with or proximity to an electrically charged conductor.

DO NOT Use the Aviation Platform Stand as a ground for Welding.

DO NOT the Aviation Platform Stand during lightning or storms.

Avoid Power Lines

Minimum Safe Approach Distance

Voltage Range (Phase to Phase)	Minimum Safe Approach Distance (Feet)	CE Guidance Note "Avoidance of danger from		
0 to 300V	Avoid Contact	overhead lines"		
Over 300 v to 50KV	10	Adhere strictly to the		
Over 50KV to 200KV	15	governmental rulings and regulations applicable to your country.		
Over 200KV to 350KV	20			
Over 350KV to 500KV	25			
Over 500KV to 750KV	35			
Over 750KV to 1000KV	45			



3.0 Safety Precautions

Know and understand the Safety Precautions before use!

Failure to heed the following safety precautions could result in tip over, falling, crushing or other hazards leading to death or serious injury.

- KNOW all national, state or territorial/provincial and local rules which apply to your Aviation Platform Stand and jobsite.
- WEAR all the protective clothing and personal safety devices issued to you or called for by job conditions.
- DO NOT wear loose clothing, dangling neckties, scarves, rings, wristwatches or other jewelry while operating this ladder.
- AVOID entanglement with ropes, cords or hoses.
- AVOID falling. Stay within the boundaries of the handrails. Overreaching, while on the ladder or platform, could cause instability and result in a fall. Always keep the unit in close proximity to work. Descend and relocate the unit to prevent overreach.
- DO NOT raise the Aviation Platform Stand in windy or gusty conditions.
- © DO NOT increase the lateral surface area of the Aviation Platform Stand. Increasing the area exposed to the wind will decrease Aviation Platform Stand stability.
- DO NOT move or elevate the Aviation Platform Stand if it is not on a firm level surface. Do not move near depressions or holes of any type, loading docks, debris, drop-offs and surfaces that may affect the stability of the Aviation Platform Stand.
- DO NOT operate on surfaces not capable of holding the weight of the Aviation Platform Stand including the rated load, e.g. covers, drains, and trenches.
- DO NOT operate a Aviation Platform Stand that has extensions, ladders, scaffolding or other devices mounted on it to increase its size or work height. It is prohibited.

- DO NOT exert side forces on Aviation Platform Stand.
- DO NOT use the Aviation Platform Stand as a crane. It is prohibited.
- © DO NOT sit, stand or climb on any part of the Aviation Platform Stand except the intended ladder rungs and platform. It is prohibited.
- DO NOT raise or lower the Aviation Platform Stand with a person or equipment on the ladder. It is prohibited.
- DO NOT move the Aviation Platform Stand with a person or equipment on the ladder or platform. It is prohibited.
- ENSURE the ladder is only raised or lowered from an operator standing on the ground.
- BE AWARE of overhead obstructions or other possible hazards around the mobile ladder stand when moving or lifting.
- DO NOT use the Aviation Platform Stand while the mobile ladder stand is on a truck, fork lift or other device or vehicle.
- BE AWARE of crushing hazards. Keep all body parts away from moving parts.
- DO NOT lower the ladder unless the area below is clear of personnel and obstructions.
- BE AWARE of blind spots when operating the Aviation Platform Stand.
- STUNTS and horseplay are prohibited.
- ENSURE all wheel brakes are locked, outrigger jacks are down (if equipped) and mobile ladder stand is level prior to climbing ladder.
- DO NOT exceed the rated capacity of the Aviation Platform Stand.
- DO NOT position the mobile ladder stand against another object to steady the platform.

Ascending and descending the ladder shall only be done using three points of contact.

- Use only equipped ladder for ascending and descending.
- Do use three points of contact ascending and descending the ladder. Face the ladder when entering and exiting.
- Three points of contact means that two hands and one foot or one hand and two feet are in contact with the ladder or the ground at all times during ascending or descending.

An operator should not use any mobile ladder stand that:

- Does not appear to be working properly.
- Has been damaged or appears to have worn or missing parts.
- Has alterations or modifications not approved by the manufacturer.
- Has safety devices which have been altered or disabled.
- Has been tagged or blocked out for non-use or repair.

Failure to avoid these hazards could result in death or serious injury



4.0 Inspections

4.1 Job Site Inspection

Do not use in hazardous locations.

Perform a thorough jobsite inspection prior to operating the Aviation Platform Stand, to identify potential hazards in your work area.

Be aware of moving equipment in the area. Take appropriate actions to avoid collision.

4.2 Maintenance and Inspection Schedule

The actual operating environment of the Aviation Platform Stand governs the use of the maintenance schedule. The inspection points covered in Table 1.2 Maintenance and Inspection Checklist indicates the areas of the mobile ladder stand to be maintained or inspected and at what intervals the maintenance and inspections are to be performed.

4.3 Owner's Annual Inspection Record

It is the responsibility of the owner to arrange quarterly and annual inspections of the Aviation Platform Stand. Table 1.1 Owner's Annual Inspection Record is to be used for recording the date of the inspection, owner's name, and the person responsible for the inspection of the Aviation Platform Stand.

4.4 Replacement Parts

Use only original replacement parts. Parts such as wheels, handrails, etc. with weight and dimensions different from original parts will affect stability of the Aviation Platform Stand and must not be used without manufacturer's consent.



5.0 First Use Instructions

Inspect all components of the Aviation Platform Stand prior to assembling and report any missing or damaged components to Liftsafe Engineering & Service Group Inc.

- The Aviation Platform Stand is typically shipped fully assembled, though sometimes this may not be the case, in these circumstances separate instructions regarding assembly will be included.
- Check all hardware on the Aviation Platform Stand to ensure nothing has become loose during shipping.
- Complete a start-up annual inspection and full function test prior to first use (refer to table 1.2).

6.0 Maintenance, Inspection and Service

Any unit that is damaged or not operating properly must be immediately tagged and removed from service until proper repairs are completed.

6.1 Maintenance and Service Safety Tips

- Maintenance and repair should only be performed by personnel who are trained and qualified to service this mobile ladder stand.
- All maintenance and service procedures should be performed in a well-lit and well ventilated area.
- Anyone operating or servicing this Aviation Platform Stand must read and completely understand all operating instructions and safety hazards in this manual.
- All tools, supports and lifting equipment to be used must be of proper rated load and in good working order before any service work begins. Work area should be kept clean and free of debris to avoid contaminating components while servicing.
- All service personnel must be familiar with employer and governmental regulations that apply to servicing this type of equipment.
- Keep sparks and flames away from all flammable or combustible materials.
- Properly dispose of all waste material such as lubricants, rags, and old parts according to the relative law provisions obtaining in the country.

6.2 Maintenance and Inspection

Death or injury can result if the Aviation Platform Stand is not kept in good working order. Inspection and maintenance should be performed by competent personnel who are trained and qualified on maintenance of this Aviation Platform Stand.

Failure to perform each procedure as presented and scheduled may cause death, serious injury or substantial damage.

NOTE: Preventive maintenance is the easiest and least expensive type of maintenance.

- Unless otherwise specified, perform each maintenance procedure with the Aviation Platform Stand in the following configuration:
- Aviation Platform Stand parked on a flat and level surface with wheel brakes engaged.
- Repair any damaged or malfunction components before operating Aviation Platform Stand.
- Keep records on all inspections.

6.3 Maintenance Instructions

This manual consists of four schedules to be done for maintenance on an Aviation Platform Stand. Inspection schedule frequency is shown below:

Inspection Schedule

Daily A
Frequently A + B
Annually A + B + C
Bi-Annually A + B + C + D

- Make copies of the maintenance and inspection checklist to be used for each inspection.
- Check the schedule on the checklist for the type of inspection to be performed.
- Place a check in the appropriate box after each inspection procedure is completed.
- Use the maintenance and inspection checklist to perform these inspections.
- & If any inspection receives a fail, tag and remove the aerial platform from service.



LEGEND				
P=PASS	F=FAIL	R=REPAIRED		

Table 1.1 Owners Annual Inspection

Model Number:				Serial Number:					
Recording	1	2	3	4	5	6	7	8	9
Date									
Recording Year									
Owners Name									
Inspected By									

Table 1.2 Maintenance and Inspection Checklist

If any Aviation Platform Stand component(s) has been repaired, an inspection must be performed again before removing the tag. Place a check in the repair column.

Serial Number:	Operators Name:
Model Number:	(Please Print)
Date:	Operator's Signature:
Time:	

As each item is inspected, write the appropriate grade in the box.

P=PASS F=FAIL R=REPAIRED

A: Perform Visual and Daily Maintenance Inspections & Functions Test

B: Perform scheduled Maintenance Inspection every three months based on regular

C: Perform scheduled Maintenance Inspection every year

Schedule		Р	F	R
Inspection Point				
Labels	A+B+C			
Wheel Brakes	A+B+C			
Caster Swivel Locks	A+B+C			
Foot Pump	A+B+C			
Cylinder	A+B+C			
Oil Level	A+B+C			
Leveling Jacks	A+B+C			
Ladder Structure	A+B+C			
Base Frame Structure	A+B+C			
Hand Rails	A+B+C			
Bumpers	A+B+C			
Directional Control Valve	A+B+C			
Hardware	A+B+C			
Platform	A+B+C			
Fall Arrest Anchor Point	A+B+C			
Folding Hand Rails	A+B+C			
Function Test	A+B+C			

NOTE: Make a copy of this page

7.0 Replacement Parts List

Item	Part Number	Description
1	V01661	DOCUMENT HOLDER
2	V01663	HYD OIL AW32
3	V01660	FALL ARREST ANCHOR POINT
4	V01659	HYD CYLINDER: 2.5 BORE x 30 STROKE
5	V01658	FOOT OPERATED PISTON PUMP
6	V01657	DIRECTIONAL CONTROL VALVE
7	V01654	HYDRAULIC STAND WELDMENT
8	V01642	RINGBOLT 5/16
9	V01641	CHAIN GUARD
10	V01636	JACK WELDMENT
11	V01632	JACK WELDMENT MOUNTING PLATE
12	V01083	TOP PLATFORM WITH TOP STAIRS ASSEMBLY
13	V01082	BASE AND CES RAIL ASSEMBLY
14	V00991	BLICKLE 10" CASTER
15	V00985	BLICKLE 6" CASTER
16	V00984	RAIL END STOP
17	V00974	TROLLEY
18	V00439	RAILING HINGE
19	V00386	RIGHT SIDE HAND RAIL WELDMENT
20	V00379	LEFT SIDE HAND RAIL WELDMENT
21	V00349	GRIP SPAN



7.1 Approved List of Hydraulic Fluids and Lubricants


Fluids:

AW32 Hydraulic Oil

Lubricants:

& N/A

Parts Drawing



8.0 Regular Operation Procedure

8.1 Regular Operation Procedure

- Ensure free of tools, equipment, and personnel
- Ensure safety of Aviation Platform Stand
- Ensure safety of operating area
- Locate Aviation Platform Stand in operating area
- Disengage and stow tow bar (If Equipped)
- Engage wheel locks (Figure 1)
- Engage leveling legs (Figure 2)
- Ascend ladder partially and erect platform railings (Figure 3)
- Keep hands/feet clear of all moving parts during operation
- Raise grab handles by pulling quick release pin and moving handle to top wait for it to click into position (Figure 6) (Figure 7)
- From the ground, install platform railing safety pins (Figure 4)
- Hold black hydraulic lever either towards the platform to raise the platform or pull back towards the operator to lower the platform (Figure 5)
- Begin to pump using foot lever to either raise or lower (Figure 5)
- Secure one's self using fall arrest anchor (Figure 9)
- Install safety chains

NOTE: For Figure Drawings Please See Next Page



Figure 1



Figure 2



Figure 3



Figure 4



Figure 5



Figure 6



Figure 7



Figure 8



Figure 9

8.2 After Use

- Ensure platform is free of all equipment, tools, and personnel
- Decouple and stow safety chains
- Ensure area below and around platform is clear of obstructions
- Pump platform to storage height
- Lower grab handles (Figure 6)
- Remove safety pins (Figure 4), Unlock hinges (Figure 3)
- Raise leveling legs (Figure 2)
- Disengage wheel locks (Figure 1)
- Store Aviation Platform Stand in a safe, dry location

8.3 Tow Bar (If Equipped)

- Do not tow while platform is raised
- Do not tow while tools, equipment, or personnel are on the Aviation Platform Stand
- Do not tow over 10km/h (6mph)

NOTE: Figures are depicted on pervious page

Aviation Platform Stand Model# DF071556 — 03(XP) Maintenance and Operation

9.0 Notes



Liftsafe Fall Protection 409 Harmony Road

Ayr, Ontario NOB 1E0

TF.: 1 (800) 977-2005

T.: (519) 896-2430

F.: (519) 896-2085

E.: info@liftsafeinspections.com

W.: www.fallsafetysolutions.com