



LANDING GEAR CHANGE STAND

DESCRIPTION

This set of stands creates a safe, efficient solution in accessing the landing gear and wheel well areas. These units can be built to meet the requirements of any aircraft landing gear configuration. The stand is an adjustable-height maintenance platform designed for service on landing gear assemblies and wheel bay access positions. The platform can be used either as a set or individually, based on the work to be performed. The platform is easily manoeuvred with telescoping handrails, while being fully compliant with global standards and regulations.

This unit also works as a daily maintenance stand; the freestanding modules are designed for regular maintenance and inspection of your aircraft. These dynamic platforms are capable of being used alone or quickly linked together to form a complete work platform system. These lightweight platforms offer unmatched stability and durability when used in an array of applications.

Our Professional Engineers can design custom models based on your specific requirements.

WHAT OUR CUSTOMERS ARE SAYING

"We find that Liftsafe Fall Protection is more than willing to work with us in creating safe, economical and multi-purpose designed equipment, tailored to our needs."

BENEFITS

- Fall protection anchor points
- Efficient solution in accessing the landing gear and wheel well areas
- Can be built to meet the requirements of any aircraft landing gear scenario
- Adjustable-height maintenance platform designed for service on landing gear struts and wheel bay access position
- Platform can be used as a set or separately
- Easy manoeuvrability
- Unmatched stability and durability



NATO N/CAGE CODE: L03Y4



member of

NBAA



PRODUCT FEATURES

- Adjustable-height maintenance platform
- Telescoping handrails
- Fall restraint anchorage (if required)
- Lightweight yet durable design
- Unmatched stability versus conventional ladder platforms
- Flexible design can be used in an array of applications
- Polished aluminum finish
- Fail-safe hydraulic cylinder locks
- Stainless steel hardware
- Split wheel castors for easy movement
- Designed and tested in accordance with ANSI-ASC A14.7 and BS EN 131.7, DIN EN 12312-8, EN 1915-1, and includes CE Certification

- Lightweight construction
- Low maintenance finish
- 2 year limited warranty on components
- 10 year limited warranty on structure



LANDING GEAR CHANGE STAND

AVAILABLE ACCESSORIES

- Custom sizes and heights
- Fork pockets
- Fold away tow bar
- Utilities package



TECHNICAL SPECIFICATIONS

DF071559-01

DESIGNED FOR	Landing Gear Access
AIRCRAFT TYPE	B737 (Pictured, Other Models Available)
MOVEMENT	1 Person
TOWING SPEED	6 MPH / 10 KPH
FOOTPRINT ASSEMBLED	73 5/16" x 196 1/4" / 186.2cm x 498.4cm
SHIPPING (DIMS)	73 5/16" x 36 1/16" x 96" x 430 lbs x 2 Stands / 186.2cm x 91.5cm x 243.8cm x 195kg x 2 Stands
HEIGHT	36 1/10" / 91.6cm to 50 1/2" / 128.2cm
WEIGHT CAPACITY	660 lbs / 300 kg each
CERTIFICATIONS	ANSI-ASC A14.7, BS EN 131.7, CE, DIN EN 12312-8 & EN 1915-1
MATERIAL	Stairs: Aluminum Frame: Aluminum
FINISH	Polished Aluminum
NUMBER OF USERS	2 Users
CASTOR DETAILS	8" / 20.3cm Split Castor with Brake and Swivel Lock
FALL RESTRAINT ANCHOR POINTS	Equipped