
# Pure Effect.

# PEV-3,000 CARBON VESSEL

## **Product Specification Sheet**


### DESCRIPTION

- Pure Effect's PEV-3,000 vapor phase carbon vessels are designed for the removal of contaminants from air streams, with flow ranges up to 3,000 cfm per unit and carbon capacity of 3,000 pounds.
- The PEV-3,000 vessels are designed and manufactured non-code. The materials used in construction are in accordance with standards established by local, state, and federal environmental standards.
- Typical applications for this line of filters include reduction of VOC concentrations, corrosive gases, toxic vapors and odor control.




### **FEATURES**

- Vessels are constructed of high grade carbon steel, with high solids epoxy lining and exterior paint of industrial enamel or urethane.
- Top access port of 18" dia. manway.
- Forklift tubes for portability.



### **TECHNICAL**

- Max fill: 3,000 lbs. granular activated carbon (GAC)
- Max pressure: 15 psi
- Design flow rate: 3,000 cfm
- Max operating temp: 140° F
- Overall dimensions: 60" x 60" x 93"
- Inlet and outlet size: 4" or 6" NPT threaded
- Total volume: 137 ft<sup>3</sup>
- Shipping weight with carbon fill: 4,900 lbs.



Adhere to all applicable health & safety regulations when using this product.

601 W. Valencia Drive, Fullerton CA 92832 Phone: 714-639-7873 Fax: 714-639-8530 www.pureeffect.com