

Tailored ventilation

Philips Respironics BiPAP A40 - because every patient is different

Because our innovations are inspired by you and your patients, the bi-level ventilator BiPAP A40 has been designed to combine ease-of-use and comfort with technological innovations that adapt to your patient's condition to deliver enhanced therapy. Based on a familiar platform, BiPAP A40 comes with well-known and clinically proven Philips Respironics technology such as Auto-Trak, AVAPS and a Dry Box humidifier design. The device is capable of non-invasive and invasive pressure ventilation, up to 40 cmH<sub>2</sub>O, providing treatment for your chronic insufficiency respiratory patients.

BiPAP A40 can provide autonomy and increased support to patients, thanks to its specifically designed battery module. The device features AVAPS-AE, an innovative mode of ventilation designed to help clinicians during the titration process, while maintaining comfort and therapy optimization. This new ventilation mode helps in providing long-term therapy compliance regardless of changes to the body position, sleep stages and respiratory mechanics.



## AVAPS-AE mode

In AVAPS-AE mode, the device monitors the patient's upper airway resistance and automatically adjusts the delivered EPAP required to maintain an airway. Simultaneously, BiPAP A40 automatically adjusts pressure support to maintain a target tidal volume and when the breath rate is set to Auto, the device will adjust the back-up breath rate based on the patient's spontaneous respiratory rate.

Ordering information	Part no.
Devices	
BiPAP A40, International*	1111169
BiPAP A40, Australia*	1111171
BiPAP A40, Canada*	1111173
BiPAP A40 Canada, Heated Tube core pkg	1111174
* contains BiPAP A40 ventilator with SD card, power cord,	

AC power adapter, user manual, ultra fine filter, grey foam filter, tubing, and carrying case

Accessories	
A-Series humidifier, International	1111552
A-Series, heated tube humidifier, International	1111555
Battery module	1096770
Detachable battery	1043570
Ultra fine filter kit	1063096
Foam filter kit	1063091
Power supply	1081167
Power cord, Europe	1039014
Power cord, UK	1039026
Power Cord, Canada	1038928
Performance tubing 22 mm	1032907
Performance tubing 15 mm	1074400
EncorePro 2 software	1054785
DirectView software	1005297
RJ9 to 1/4" nurse call cable, closed	1080247
RJ9 to 1/4" nurse call cable, open	1080248
RJ9 nurse call cable, open ends	1080249
Carrying bag	1098514
BiPAP A40 in-use bag	1098513
Oximetry accessory, INTL	100215E
Oximetry Accessory, DOM	100205E
BiPAP A Series roll stand	1098538

## **Product specifications**

Product specificatio	ns
Ventilation modes	• CPAP • S • S/T • PC • T • AVAPS-AE
Hybrid ventilation	<ul> <li>AVAPS (Average Volume Assured Pressure Support)</li> <li>AVAPS-AE</li> </ul>
IPAP	$4-40 \text{ cmH}_2\text{O}$
EPAP	4 – 25 cmH <sub>2</sub> O
Target tidal volume (AVAPS & AVAPS-AE)	200 – 1500 ml
Breath rate	0 – 40 bpm (4 – 40 bpm in T mode)
Inspiratory time	0.5 – 3 sec.
Triggering and cycling	• Auto-Trak • Sensitive Auto-Trak • Flow triggering
Rise time	1 (100 ms) – 6 (600 ms)
Size	21.6 cm W x 19 cm L x 11.5 cm H
Weight	1.9 kgs (with power supply)
Noise level	< 28 dBA at 10 cmH <sub>2</sub> O
Humidification	<ul><li>System One humidity control and</li><li>'Dry Box' technology</li><li>Heated tube humidification</li></ul>
Alarms	<ul> <li>Patient disconnection</li> <li>Apnea</li> <li>Low minute ventilation</li> <li>Low tidal volume (with AVAPS/AVAPS-AE only)</li> <li>High respiratory rate</li> </ul>
Monitoring	<ul> <li>Pressure • Tidal volume • Minute ventilation</li> <li>Respiratory rate • Leak • I/E ratio</li> </ul>
Battery back up	Detachable battery module: 9h 45 min at IPAP 12 $cmH_2O/EPAP$ 7 $cmH_2O$ and 12 bpm (restrictive profile)
DC power source	<ul> <li>12 VDC, 5.0 A (external battery)</li> <li>24 VDC, 4.2 A (power supply)</li> </ul>
Data management	<ul> <li>Encore and DirectView software</li> <li>Compatible with oximetry module</li> <li>Advanced detection of residual respiratory events (apnea/hypopnea index, obstructed airway apnea, hypopnea, periodic breathing, RERA, large leak and snore)</li> </ul>
Remote control	Compatible with Omnilab Direct
Polygraph and polysomnograph connections	<ul> <li>Direct connection to Alice PDx and Alice6 PSGs</li> <li>Omnilab Connect to connect to most PSG systems</li> </ul>

BiPAP A40, Auto-Trak, AVAPS, AVAPS-AE, EncorePro, DirectView, and Alice are trademarks of Koninklijke Philips N.V. All rights are reserved.

## Please visit www.philips.com/respironics



© 2014 Koninklijke Philips N.V.All rights are reserved.

Philips Healthcare reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

CAUTION: US federal law restricts these devices to sale by or on the order of a physician.

Broudy RP 3/14/14 MCI 4106085 PN 1102086

Philips Regionalise 15 at 01 Koya 17 Philips Regionalis Asia Pacific +65 6892 5282 Philips Regionalis Australia +61 (2) 9947 0440 Philips Regionalise Benelux +33 1 47 28 30 83 Philips Regionalise Canada +1 724 387 4000 Philips Regionalise Journala +1 8152 93 06 0 Philips Regionalise Trance +33 2 51 89 36 00

Philips Healthcare is part of Royal Philips

Philips Respironics Italy +39 039 203 1 Philips Respironics Sweden +46 & 120 45 900 Philips Respironics Switzerland +41 6 27 45 17 50 Philips Respironics United Kingdom +44 800 1300 845 Philips Respironics 1010 Murry Ridge Lane Murry Swile, PA 15668 USA