

imageRUNNER ADVANCE DX 4800 Series

Print up to 45 ppm (BW)

Scan up to 270 ipm (300 dpi) (BW/color, duplex)

Print up to 12" × 18"

3,650-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.

Black-and-white
Mid-volume
Multifunction



WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive.¹
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.
- Hot Folders allow users to drag and drop a file into a hot folder, and automatically print with predefined settings such as number of copies and finishing requirements.



SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM*² systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at startup. McAfee Embedded Control³ utilizes a whitelist to protect against malware and tampering of firmware and applications.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.⁴



QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for crisp text and consistent images in rich black-and-white tones.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE DX models have received many awards and recognition from leading industry analysts, often referencing strong reliability.

* Security Information and Event Management



DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-the-minute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified and rated EPEAT® Gold.⁵

CONFIGURATION OPTIONS

imageRUNNER ADVANCE DX 4800 Series

INNER 2 WAY TRAY-MI

INNER FINISHER-L1

- 2-tray, 550-sheet capacity
- Corner and double stapling up to 50 sheets within the footprint of the main unit
- Supports Staple-free Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (Inner 2/3 Hole Puncher-D1)

SINGLE PASS DADF-C1

- Up to 200-sheet capacity
- Scan speed up to 270 ipm (BW/Color)

DADF-BA1

- Up to 100-sheet capacity
- Scan speed up to 35 ipm (BW/Color)

Options for the 4835i/4825i models. Single Pass DADF is standard on the 4845i model.

BOOKLET FINISHER-AE1

- 2-tray, 3,250-sheet capacity
- Corner and double stapling up to 50 sheets
- Booklet-making up to 20 sheets and saddle-folding up to 3 sheets
- Supports Staple-free Stapling* and Staple On Demand
- Supports optional 2/3-hole puncher (2/3 Hole Puncher Unit-A1)

STAPLE FINISHER-AE1

- 2-tray, 3,250-sheet capacity
- Corner and double stapling up to 50 sheets
- Supports Staple-free Stapling* and Staple On Demand
- Supports optional 2/3-hole puncher (2/3 Hole Puncher Unit-A1)

UTILITY TRAY-B1

COPY TRAY KIT

CASSETTE FEEDING UNIT-AWI

- Two 550-sheet cassettes
- Supports up to 12" x 18"
- Supports 14 lb. Bond to 140 lb. Index

HIGH-CAPACITY CASSETTE FEEDING UNIT-E1

- 2,450-sheet capacity
- Supports LTR
- 140 lb. Bond to 140 lb. Index

CABINET TYPE-W

Not Shown

- Inner 2/3 Hole Puncher-D1 (for Inner Finisher-L1)
- 2/3 Hole Puncher Unit-A1 (for External Finishers)
- Platen Cover Type-Y3

* Staple-Free stapling, up to 5 pages of 17 lb. Bond.

SPECIFICATIONS

imageRUNNER ADVANCE DX 4800 Series

Main Unit

Type
Monochrome Laser Multifunctional

Core Functions
Standard: Print, Copy, Scan, Send, Store
Optional: Fax

Processor
1.8 GHz Dual Core Processor

Control Panel
10.1" TFT LCD WSVGA Color Touch-panel

Memory
3.5 GB RAM

Solid State Drive
Standard: 256 GB
Maximum: 1 TB

Print Resolution
1200 dpi x 1200 dpi

Interface Connection

Network
Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)
Optional: Bluetooth Low Energy

Others
Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device)
Optional: Copy Control Interface, Serial Interface

Paper Capacity (LTR, 20 lb. Bond)
Standard: 1,200 Sheets
Maximum: 3,650 Sheets

Paper Sources (LTR, 20 lb. Bond)
Standard: Two 550-sheet Paper Cassettes, 100-sheet Stack Bypass
Optional: High-Capacity Cassette Feeding Unit-E1 (2,450 sheets)

Paper Output Capacity (LTR, 20 lb. Bond)
Standard: 250 Sheets
Maximum: 3,450 Sheets (with Staple Finisher-AE1 or Booklet Finisher-AE1 and Copy Tray-T2)

Finishing Capabilities
Standard: Collate, Group
With Finishers: Collate, Group, Offset, Staple, Saddle-Stitch, Hole Punch, Staple-Free Stapling, Staple On Demand

Supported Media Types
Upper Cassette: Thin, Plain, Heavy, Recycled, Color, Bond, Pre-punched, Letterhead, Envelope
Multi-purpose Tray: Thin, Plain, Heavy, Recycled, Coated, Color, Tracing, Bond, Label, Pre-punched, Letterhead, Envelope

Supported Media Sizes
Upper Cassette: Standard size: Letter, Executive, Statement-R
Custom Size: 4-1/8" x 5-7/8" to 11-3/4" x 8-1/2" (105.0 mm x 148.0 mm to 297.0 mm x 215.9 mm)
Envelopes: ISO-C5
Lower Cassette: Standard size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R
Custom Size: 4-1/8" x 5-7/8" to 12" x 18" (105.0 mm x 148.0 mm to 304.8 mm x 457.2 mm)
Envelopes⁶: COM10 No.10, Monarch, DL
Multi-purpose Tray: Standard size: 12"x18", 11"x17", Legal, Letter, Letter-R, Executive, Statement, Statement-R
Custom size: 3-7/8" x 5-1/2" to 12-5/8" x 18" (98.4 mm x 139.7 mm to 320.0 mm x 457.2 mm)
Free size: 4" x 5-7/8" to 12" x 18" (100.0 mm x 148.0 mm to 304.8 mm x 457.2 mm)
Envelopes: COM10 No.10, Monarch, ISO-C5, DL
Envelope custom size: 3-7/8" x 3-7/8" to 12-5/8" x 18" (98.0 mm x 98.0 mm to 320.0 mm x 457.2 mm)

Supported Media Weights
Upper/Lower Cassette: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²)
Multi-purpose Tray: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

Print/Copy Speed (One-sided)
4845i: Up to 45 ppm (Letter), Up to 22 ppm (Legal/11"x17"), Up to 32 ppm (Letter-R)
4835i: Up to 35 ppm (Letter), Up to 17 ppm (Legal/11"x17"), Up to 23 ppm (Letter-R)
4825i: Up to 25 ppm (Letter), Up to 15 ppm (Legal/11"x17"), Up to 20 ppm

Warm-up Time
From Power On: Approx. 10 Seconds or Less⁷
From Sleep Mode: Approx. 10 Seconds⁸
Quick Startup Mode: Approx. 4 Seconds⁹

Dimensions (W x D x H)
With Platen Cover-Y3: 22-1/4" x 27-1/4" x 31" (565 mm x 692 mm x 788 mm)
With Single Pass DADF-C1: 22-1/4" x 28-1/2" x 35-3/8" (565 mm x 722 mm x 897 mm)
With DADF-BA1: 22-1/4" x 28-3/8" x 35-1/8" (565 mm x 719 mm x 891 mm)

Installation Space (W x D)
Basic: 38-1/2" x 44-1/8" (978 mm x 1119 mm) (with Single Pass DADF-C1 + right door and multipurpose tray opened + paper cassette opened)
38-1/2" x 45" (978 mm x 1116 mm) (with DADF-BA1 + right door and multipurpose tray opened + paper cassette open)
Fully Configured: 65" x 44-1/8" (1651 mm x 1119 mm) (with Single Pass DADF-C1 + Staple Finisher-AE1/Booklet Finisher-AE1 + Copy Tray-T2 extended + paper cassette open)
1651 mm x 1116 mm (with DADF-BA1 + Staple Finisher-AE1/Booklet Finisher-AE1 + Copy Tray-T2 extended + paper cassette open)

Weight¹⁰
With Platen Cover-Y3: Approx. 134.5 lb. (61 kg)
With Single Pass DADF-C1: Approx. 163.1 lb. (74 kg)
With DADF-BA1: Approx. 149.9 lb. (68 kg)

Print Specifications

Standard Page Description Languages
UFR II, PCL[®] 6, Adobe[®] PS[®] 3

Supported File Types for Direct Print
PDF, TIFF, JPEG, EPS, XPS

Printing from Mobile Devices and Cloud-based Services
A range of standard and optional software and MEAP-based solutions (including AirPrint, Mopria, Universal Print by Microsoft[®], Canon PRINT Business, and uniFLOW Online) are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.

Fonts
PCL: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),¹¹ Barcode Fonts¹²
PS: 136 Roman

Operating System¹³
UFR II: Windows[®] 8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, Mac OS X (10.11 or later)

PCL: Windows[®] 8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022
PS: Windows[®] 8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, Mac OS X (10.11 or later)
PPD: Windows[®] 8.1/10/11, Mac OS X (10.11 or later) As of Jan. 2022

Copy Specifications

First-Copy-Out Time (Letter)
4845i: As fast as 4.6 seconds
4835i: As fast as 5.5 seconds
4825i: As fast as 6.1 seconds

Copy Resolution (dpi)
600 x 600

Multiple Copies
Up to 9,999 Copies

Copy Exposure
Automatic or Manual (9 Levels)

Magnification
25%-400% (1% Increments)

Preset Reduction/Enlargement
25%, 50%, 64%, 73%, 78%, 100% (1:1), 121%, 129%, 200%, 400%

Scan Specifications

Type
Standard: Color Platen
Optional: Platen Cover-Y3, Single Pass DADF-C1¹⁴ or DADF-BA1 [2-sided to 2-sided (Automatic with DADF)]

Document Feeder Paper Capacity
Single Pass DADF: Up to 200 Sheets
DADF: Up to 100 Sheets

Document Feeder Supported Media Sizes
11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

Document Feeder Supported Media Weights

Single Pass DADF-C1
Single-sided Scanning: 13.3 lb. Bond to 80 lb. Cover (50 to 220 g/m²)
Double-sided Scanning: 13.3 lb. Bond to 80 lb. Cover (50 to 220 g/m²)
DADF-BA1
Single-sided Scanning: 13.3 lb. Bond to 34 lb. Bond (50 to 128 g/m²) (BW), 17 lb. Bond to 34 lb. Bond (64 to 128 g/m²) (CL)
Double-sided Scanning: 13.3 lb. Bond to 34 lb. Bond (50 to 128 g/m²) (BW), 17 lb. Bond to 34 lb. Bond (64 to 128 g/m²) (CL)

Platen Acceptable Originals
Sheet, Book, 3-Dimensional Objects

Platen Supported Media Size
Up to 11-3/4" x 17" (297 mm x 431.8 mm)

Pull Scan
Color Network ScanGear2 for both Twain and WIA
Supported OS: Windows[®] 8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022

Scan Resolution (dpi)
Push: Up to 600 x 600
Pull: Up to 600 x 600

Scan to Mobile Devices and Cloud-based Services
A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

Scan Speed (Letter)
Single Pass DADF-C1
Single-sided Scanning
BW/Color: 135/135 (300 x 300 dpi, send), 80/80 (600 x 600 dpi, copy)
Double-sided Scanning
BW/Color: 270/270 (300 x 300 dpi, send), 160/90 (600 x 600 dpi, copy)

DADF-BA1
Single-sided Scanning
BW/Color: 70/70 (300 x 300 dpi, send), 51/51 (600 x 600 dpi, copy)
Double-sided Scanning
BW/Color: 35/35 (300 x 300 dpi, send), 25.5/25.5 (600 x 600 dpi, copy)

Send Specifications

Destination
 Standard: Email/Internet FAX (SMTP), SMB 3.1.1, FTP, WebDAV, Mail Box Optional: Super G3 FAX, IP Fax
 Optional: Super G3 Fax, IP Fax

Address Book
 LDAP (2,000)/Local (1,600)/Speed dial (200)

Send Resolution (dpi)
 Push: Up to 600 x 600
 Pull: Up to 600 x 600

Communication Protocol
 File: FTP (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV
 Email/Fax: SMTP (Send), POP3 (Receive)

File Format
 TIFF, JPEG, PDF (Compact, Searchable, Apply Policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

Fax Specifications (Optional)

Maximum Number of Connection Lines
 4

Modem Speed
 Super G3: 33.6 Kbps
 G3: 14.4 Kbps

Compression Method
 MH, MR, MMR, JBIG

Resolution (dpi)
 400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size
 Statement-R to 11" x 17"

Fax Memory
 Up to 30,000 Pages (2,000 Jobs)

Speed Dials
 Max. 200

Group Dials/Destinations
 Max. 199 Dials

Sequential Broadcast
 Max. 256 Addresses

Memory Backup
 Yes

Store Specifications

Mail Box (Number Supported)
 100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes, Maximum 30,000 Pages (2,000 Jobs) Stored

Advanced Box
 Communication Protocol: SMB or WebDAV
 Supported Client PC: Windows (Windows 8.1/10)
 Concurrent Connections (Max.):
 SMB: 64
 WebDAV: 3 (Active Sessions)

Advanced Box Available Disk Space
 Approx. 16 GB (Standard HDD)
 Approx. 480 GB (With Optional 1 TB HDD)

Memory Media
 Standard: USB

Security Specifications

Authentication
 Standard: Universal Login Manager, uniFLOW Online Express,¹⁵ User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in
 Optional: uniFLOW

Data
 Standard: Protecting SSD Data [SSD Data Encryption (FIPS140-2 Validated), SSD Lock], Standard SSD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFP Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection), Common Criteria Certification (HCD-PP) (pending confirmation)³
 Optional: Hard Disk Drive Mirroring, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network
 Standard: TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), WPA3 support (Wi-Fi), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), Communication Line Separation (G3 FAX, USB Port, Advanced Space, Scan and Send-Virus Concerns for Email Reception)

Document
 Standard: Secure Watermark, Secure Print, Forced Hold Printing, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature, User Signature

Environmental Specifications

Operating Environment
 Temperature: 50 to 86°F
 Humidity: 20 to 80% RH (Relative Humidity)

Power Requirements
 110 - 127 V 60 Hz, 8.5 A

Power Consumption
 Maximum: Approx. 1,500 W
 Copying (with DADF continuous scan):
 Approx. 649 W (110 - 127 V)
 Approx. 37.8 W (110 - 127 V)¹⁶
 Standby: Approx. 0.8 W¹⁷
 Sleep Mode: Approx. 0.8 W¹⁷
 Typical Electricity Consumption (TEC) Rating¹⁸
 4845i: 0.48 kWh
 4835i: 0.37 kWh
 4825i: 0.27 kWh

Standards
 ENERGY STAR® Certified
 Rated EPEAT® Gold⁵

Consumables

Toner
 GPR-64 Toner BK

Toner Yield (Estimated @ 6% Coverage)
 Black: 42,000 Pages

¹ Subscription to a third-party cloud service required. Subject to third-party cloud service provider's Terms and Conditions.
² Third-party SIEM system required. Subject to third-party SIEM system's Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.
³ This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on.
⁴ Requires additional option.
⁵ For current EPEAT rating (Gold/Silver/Bronze), please visit www.epeat.net.
⁶ Envelope Attachment A (standard) is required.
⁷ Time from device power-on until copy ready (not print reservation).
⁸ Time from exiting Sleep mode to when printing is operational.
⁹ Time from device power on to when the copy icon appears and is enabled to operate on the touch panel display.
¹⁰ Includes toner.
¹¹ Requires the optional PCL International Font Set-A1.
¹² Requires the optional Barcode Printer Kit-D1.
¹³ Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
¹⁴ Detect Feeder Multi Sheet Feed is supported.
¹⁵ No charge for this solution; however, activation is required.
¹⁶ Reference Value (measured one unit).
¹⁷ 0.8 W Sleep mode not available in all circumstances due to certain settings.
¹⁸ Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.

AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Some security features may impact functionality/performance; you may want to test these settings in your environment. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. McAfee and the McAfee logo are trademarks of McAfee LLC in the US and/or other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.
 ©2022 Canon U.S.A., Inc. All rights reserved.



usa.canon.com



To learn about Canon's many awards, visit usa.canon.com/awards.