## Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be Consulted for specific requirements.

## U.S. Department of Labor

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List) Solder Mask Water Soluble 515°			Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.						
Section I									
Manufacturer's Name Metron Optics, Inc.			Emergency Telephone Number 858-755-4477						
Address (Number, Street,	809 Academy Drive		Emergency Telephone Number						
	-		Date Prepared (mm-dd-yy)						
	Solana Beach, CA - USA		January, 2024— Rev3						
			Signature of Preparer (Optional)						
SECTION II —H	azardous Ingredients/Ide	entity Informat	ion						
	pecific Chemical Identity; Common Name(s)	OSHA PEL	ACGIH-TLV	Other Limits (Recommended)	% (Optional)				
	CAS#		Wt. % Range:						
Deionized water	r 7732-18-5		40.0—50.0						
Acrylic Polymer	Mixture		25.0—30.0						
Aluminum Silica	ate 8031-18-3		5.0—10.0						
Glycerin	56-81-5		1.0—5.0						
Isopropanol	67-63-0		1.0—5.0						
Titanium dioxid	le 13463-67-	-7	0.1-1.0						
Carboxylic acid	Proprietary	Y	10.0 - 15.0						
SECTION III -P	Physical/Chemical Chara	cteristics							
Boiling Point 200° F	-		Specific Gravity (H $_2$ O = 1) 1.00						
Vapor Pressure (mm Hg.)	12 mm Hg @ 20º C		Melting Point N/A						
Vapor Density (AIR = 1)	<1		Evaporation Rate (Butyl Alcohol = 1) > ]						
Solubility in Water	Dispersible	1	<u> </u>						
Appearance and Odor Viscous, opaque blue liquid with mild ammoniacal odor.									
SECTION IV-Fi	ire and Explosion Hazard	d Data							
Flash Point (Method Used)	None to boiling (TCC)	Flammable	Limits	LEL Not Established	UEL Not Established				
Extinguishing Media	Use Alcohol foam, carbo	n dioxide or wa	ater spray when fighting fi	re involving thi	s material.				
Special Fire Fighting Procedures As in any Fire, wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH									
approved or equivalent) and full protective gear.									
Unusual Fire and Explosion I	Hazards Spills : Shut off I	eak. Absorb s	pill with inert material (Dry	sand or earth	)				
Then place in a	Then place in a chemical waste container for proper disposal.								

SECTION V—Reactivity Data									
Stability Unstable			Conditions to Avoid						
	Stable	x	Do not spray n	ear open flames,	red hot su	irfaces or other sources of ignition			
Incompatibility (Materials to Avoid) Do not mix with powdered alkali and alkaline earth metals or strong oxidizing agents									
Hazardous Decomposition or Byproducts Thermal decomposition may release carbon monoxide, carbon dioxide and incompletely burned hydrocarbons									
Hazardous Polymerization	May Occur		Conditions to Avoid						
	Will not Occur	x	N/A						
SECTION VI —Health Hazard Data									
Route(s) of Entry: Inhalation Ingestion									
Isopropyl Alcohol LC50/rats ; 16,000ppm/8hrs LD50/rats ; 5,045 mg/kg									
Health Hazards Eyes: Liquid and vapor of this product are irritating. Skin: contact causes skin irritation. Ingestion: Harmful is swallowed. Irritating to mouth,									
throat and stomach.	May cause vomiting.	Inhalat	ion: Harmful if inhale	ed. High concentration	s of vapors in i	immediate area can displace oxygen and can cause dizzi-			
ness unconsciousness and even death with longer exposure. KEEP PEOPLE AWAY FROM VAPORS W/O SELF-CONTAINED BREATHIN APPARATUS.									
Carcinogenicity:		NTP?		IARC	Monographs?	OSHA Regulated?			
No ingredients listed as human carcinogens by NTP or IARC.									
Signs and Symptoms of E	xposure Irritatio	on, di	zziness, nause	ea. GET MEDIC	AL ATTEN	TION			
		-							
Medical Conditions Gener	ally Aggravated by Exposu	re	None Known.						
Emergency and First Aid	Procedures Fves: F			water Skin Wa	ash skin w	vith soap and water. Ingestion: In-			
duce vomitin						: GET MEDICAL ATTENTION			
	<u>,</u>								
SECTION VII	—Precautions	for S	afe Handling a	nd Use					
	Material is Released or Spi		•		ills) abso	rb spill with inert material (Dry sand			
or earth).				ricult (large sp					
or curriy.									
Waste Disposal Method	Place in a ch	emic	al waste conta	iner for proper	disnosal				
Precautions to Be Taken in Handling and Storing Precautions to Be Taken in Handling and Storing Avoid prolonged or repeated contact with eyes, skin and clothing. Use with ade-									
quate ventilation.       Other Precautions									
SECTION VIII —Control Measures Respiratory Protection (Specify Type)									
Ventilation	Local Exhaust				Special				
	Mechanical (General)				Other				
Protective Gloves				Eye Protection					
Other Protective Clothing or Equipment									
Work/Hygienic Practices Wash hands before eating									